



VDX-6350DE

256MB/4S/2USB/LAN/GPIO/PWMx16



Unit: mm

Specifications

SoC	DM&P SoC CPU Vortex86DX- 800MHz Real Time Clock with Lithium Battery Backup
Cache	L1:16K I-Cache, 16K D-Cache L2 Cache 128KB
Bus	PC/104 standard compliant PCI-104 (Optional)
BIOS	AMI BIOS
System Memory	256/512MB DDR2 Onboard
Watchdog Timer	Software programmable from 30.5 μ sec.to 512 sec. x 2 sets (Watchdog 1 fully compatible with M6117D)
Flash Disk Support	Onboard 4MB SPI Flash Disk MSTI EmbedDisk Module (16MB and above) 44-pin IDE to Micro SD (Optional)
PWM	16~24 Channels
I/O Interface	Enhanced IDE port (UltraDMA-100/66/33) x1 RS-232 port x3 RS-232/485 port x1 USB port (Ver2.0) x2 Parallel port x1 16-bit GPIO port x1 10/100Mbps Ethernet port x1
Connectors	2.0mm 44-pin box header for IDE x1 2.0mm 26-pin box header for Printer x1 2.0mm 20-pin box header for 16-bit GPIO x1 2.0mm 10-pin box header for USB x1 2.0mm 10-pin box header for RS-232 x4 2.0mm 8-pin header for Ethernet x1 2.54mm 5-pin box header for Keyboard x1 2.54mm 5-pin header for Mouse x1 2.54mm 3-pin header for RS-485 x1 2.54mm 2-pin header for Reset x1 2.54mm 7-pin header for Redundancy Signal x1 (Optional) 2.54mm 2-pin header for System-Fail-SW x1 (Optional) 1.25mm 6-pin wafer for JTAG x1
Power Requirement	Single Voltage +5V @ 400mA
Weight	77g
Board Size	90 x 96mm (3.54 x 3.77 inches)
Operating Temperature	-20°C ~ +70°C -40°C ~ +85°C (Optional)

Packing List

- VDX-6350DE x1
- CD for User's Manual & Driver x1
- Cable
HDD 44P (2.0) x1
PRINT (2.0) x1
RS-232 (2.0) x4
USB (2.0) x1
GPIO (2.0) x1
PS2 KB White x1
PS2 Mouse Black x1
- Screw Kit x1

Ordering information:

- **VDX-6350DE** Vortex86DX PC/104 CPU Module with 256MB DDR2
- **VDX-6350DE-PLUS** Vortex86DX PC/104+ CPU Module with 256MB DDR2
- **VDX-6350DE-512** Vortex86DX PC/104 CPU Module with 512MB DDR2